## PRICE LIST





🕏 تلفن تعاس: ۷۰٬۷۴۰ ۱۳۰۰ 🕟 فروشگاه سلیمانی

💆 آدرس: چهاراه شریعتی. رو به روی درب قدیم چهلستون



	• •	-	_	-			
- Ш	110	Olz.	' L'-	mh	$\sim$	HD	
	11()	( )K -	- 1		( )	- 1 I J	

It	ems	Description	User Price
	Turbo HD Cameras		
THC-B120-M	18.00 (B.2)	2 MP high-performance CMOS-1920 x 1080 resolution- 2.8 mm, fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 12,070,000
THC-B140-P	Ham B. D.	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 14,610,000
THC-T120-MS		2 MP Audio Fixed Turret Camera Smart IR, up to 20 m IR distance/Water resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS) With built-in microphone, enhancing your safety with video and audio together	IRR 16,610,000
THC-T120-M		2 MP high-performance CMOS- 1920 × 1080 resolution-2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	ناموجود
THC-T140-P		4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 14,070,000
THC-T140		4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	IRR 14,610,000
THC-T140-M		4 MP high-performance CMOS-2560 x 1440 resolution-2.8 mm, Fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL	IRR 15,150,000
THC-T220-M	5	2 MP high-performance CMOS-1920 x 1080 resolution-2.8 mm, fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 14,610,000
	IP Came	e	
IPC-B120H	8) Hi cots	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 32,300,000
IPC-B121H	E) 161 cm 25	1/2.8" progressive scan CMOS □ 3D DNR □ 1920 × 1080@30fps □ Up to 30 m IR range □ 2.8 mm/4 mm fixed lens □ IP67, DWDR, H265	IRR 27,050,000
IPC-D121H	Rosk	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR-Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	IRR 27,050,000
IPC-B140H	E Hilland 12.3	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 34,630,000
IPC-D140H	H.cox	4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440 @20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 □ IP67, IK10, Dual stream, 120 dB WDR.	IRR 39,930,000
IPC-B150H	E History 12.5	High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 44,900,000
IPC-D150H	14,000	High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 48,310,000
		Turbo HD DVR	
DVR-204G-F1	-	Recording Capability HD1080p Lite  4-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -1-ch Up to 960P resolution), 1 SATA (6TB)interface, HD1080p Lite @ 25 fps/ch, 260 1U caseHDMI output HD1080p-Metal	ناموجود

DVR-204Q-K1	-	H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTVI/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution  Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.	ناموجود					
DVR-204U-K1		Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTVI video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTVI signal	IRR 54,230,000					
DVR 8 Channel								
DVR-208G-F1		Recording Capability HD1080p Lite  8-ch- HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, 2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case—HDMI output HD1080p-Metal	ناموجود					
DVR-208Q-K1		Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable  One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite.  Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	CALL					
DVR-208U-K1		8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera ,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.2654 Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	CALL					
	DVR 16 Channel		,					
DVR-216G-K1		Recording Capability 3MP  16-ch HD-TVVAHD/CVVCVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution),  1 SATA(6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case-HDMI output 1ch 4k-Metal	IRR 55,180,000					
DVR-216U-K2		DVR 16 Channels HD 8 Megapixel, Interfaces input: 16 video / 1 Audio, (Support (TVI - AHD – CVI - CVBS, HDMI, VGA Outputs, 2 USB Support H.265+ compression, 2SATA up to 8TB capacity per HDD, Up to 8-ch, 6MP IP cameras input, Up to 8 MP resolution for recording	CALL					
	NVR							
NVR-104MH-D		Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording.	IRR 26,300,000					
NVR-108MH-D		IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, II.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 33,540,000					
NVR-116MH-C		Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 50,860,000					
NVR-216MH-C/16P		Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA( up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, Decoding Capability 1-ch @ 3 MP / 4-ch @ 1080p	موجود، تماس بگیرید					