






















































































Network Camera - NVR





















Items	Description	User Price
<b>Lite Mini Bullet Series</b>		
DS-2CV1021G0-IDW1	 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in WIFI	call
DS-2CD1021G0E-I	 Hikvision 2MP Mini IR Network Bullet camera, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps (P)(N), H.265 / H.264+ & H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE Rs. 0.001Is our price higher or showing zero? Please chat now and ask for the best price. Prices if shown are inclusive of applicable taxes. Tax rate may be adjusted as per customer's taxation status. For supply of product only, excluding any cabling and/or installation. Shipping charges can sometimes vary.	call
DS-2CD1023G0E-I	 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 26,940,000
DS-2CD1023G0-I	 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	call
DS-2CD1023G0-IUF	 2.0 MP IR Network Bullet Camera -1/2.7" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in microphone	IRR 40,770,000
DS-2CD1043G0E-I	 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range) - ECO CASE	call
DS-2CD1047G0-L ColorVu Lite	 4 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 48,590,000
DS-2CD1057G0-L	 5 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 58,820,000
DS-2CD1043G0-I	 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 35,160,000
DS-2CD1053G0-I	 5.0 MP IR Network Bullet Camera, 1/2.7" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1920@20fps - Up to 30 m IR range, 2.8 mm/4 mm fixed lens - PoE (Power over Ethernet), H.265+ , IP67, Dual stream,BLC, WDR 120 dB(Wide Dynamic Range)	call
<b>Lite Dome Series</b>		
DS-2CD1323G0E-I	 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 29,590,000
DS-2CD1323G0-IU	 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone	IRR 44,900,000
DS-2CD1323G0-IUF	 2 MP Fixed Turret Network Camera 1/2.7" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm fixed lens - H.265+ - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone,Metal & Plastic	IRR 44,900,000
DS-2CD1327G0-L ColorVu Lite	 2 MP ColorVu Lite Fixed Turret Network Camera,High quality imaging with 2 MP resolution Excellent low-light performance, Efficient H.265+ compression technology,Water and dust resistant (IP67), 24/7 colorful imaging	IRR 32,160,000
DS-2CD1347G0-L ColorVu Lite	 4 MP ColorVu Lite Fixed Turret Network Camera,High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology,Water and dust resistant (IP67), 24/7 colorful imaging	IRR 81,650,000
DS-2CD1357G0-L	 5 MP ColorVu Lite Fixed Turret Network Camera,High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology,Water and dust resistant (IP67), 24/7 colorful imaging	IRR 58,790,000
DS-2CD2327G2-L	 2 MP ColorVu Fixed Turret Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Built-in microphone for real-time audio security(-U)	IRR 81,110,000
DS-2CD2347G2-L(2.8mm)	 2 MP ColorVu Fixed Turret Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging	call
DS-2CD2347G2-LU	 4 MP ColorVu Fixed Turret Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning	IRR 89,760,000














DS-2CD1353G0-I		5 MP IR Fixed Network Turret Camera * 1/2.7" Progressive Scan CMOS, * 2560 x 1920 @15fps * Color: 0.01 Lux @(F1.2; AGC ON), 0.028 Lux @(F2.0; AGC ON), * 2.8/4/6 mm fixed lens * H.265+, H.265, H.264+, H.264 * 3D Digital Noise Reduction	call
DS-2CD2743G2-I2S		4 MP AcuSense Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal proof (IK10)	IRR 132,760,000
DS-2CD1123G0E-I		2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 26,360,000
DS-2CD1123G0-I		2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range)	call
DS-2CD2126G2-ISU 2.8mm		2 MP AcuSense Fixed Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle classification based on deep learning -SU: Built-in microphone for real-time audio security. Audio and alarm interface available	IRR 81,540,000
DS-2CD1143G0-I		4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 41,780,000
DS-2CD1143G0-IUF		High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security	call
DS-2CD1153G0-I		5 MP Fixed Dome Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range	IRR 54,540,000
DS-2CD1743G0-IZ		4 MP Varifocal Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Up to 256 GB memory card slot for storage 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67) and vandal proof (IK10)	IRR 91,340,000
DS-2CD1353G0-I 2.8mm		5MP Fixed Turret Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range	call
<b>Mini Bullet Series</b>			
DS-2CD2025FHW0-I		2 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP67), Robust structure design with full metal material.	IRR 68,530,000
DS-2CD2021G1-I		2 MP IR Fixed Network Bullet Camera - High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Support up to 256 GB SD card storage	IRR 49,980,000
DS-2CD2023G0-I		2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 37,740,000
DS-2CD2023G2-I		2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.265+ - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 59,940,000
DS-2CD2027G2-L ColorVu Lite		2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265+ - 120dB WDR - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 71,040,000
DS-2CD2043G0-I		4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 53,920,000
DS-2CD2043G2-I		4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265+ - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/HLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 66,460,000
DS-2CD2043G2-IU		4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology -U: Built-in microphone for real-time audio security	IRR 79,110,000
DS-2CD2043G0-I (Black)		4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 x 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	call
DS-2CD2047G2-L ColorVu Lite		4 MP IR Fixed Bullet Network Camera - 1/1.8" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265, H.265+ - 130dB WDR - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 77,730,000
DS-2CD2063G0-I		6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 41,620,000
DS-2CD2066G2-I		6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 78,390,000






















DS-2CD2063G2-I (2.8mm)		6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 72,800,000
DS-2CD2043G2-I		6 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+ - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 66,460,000
DS-2CD2046G2-I		4 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology	IRR 70,760,000
DS-2CD2085G1-I		8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 117,160,000
DS-2CD2083G2-I		8 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, Up to 40 m IR rsng - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB	IRR 77,710,000
DS-2CD2087G2-LU ColorVu Lite		8 MP IR Fixed Bullet Network Camera-1/1.2" Progressive Scan CMOS - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, Up to 40 m IR rsng - 2 Behavior analyses and face detection - 130dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB ,Built-in microphone	IRR 156,550,000
<b>Dome Series</b>			
DS-2CD2123G0-IS		2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128GB S: Audio/Alarm IO connectors	call
DS-2CD2123G2-IU		2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 x1080@30fps - 2.8/4mm-fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+ - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 256GB S: Audio/Alarm IO connectors, Up to 30 m IR range	IRR 61,350,000
DS-2CD2125FHDW-IS		2 MP High Frame Rate Fixed Dome Network Camera, High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology High frame rate video to illustrate smooth movement, -S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10). Robust structure design with full metal materials	IRR 49,060,000
DS-2CD2H25FWD-IZS		2 MP Powered-by-DarkFighter Varifocal Turret Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10)	IRR 138,870,000
DS-2CD2143G2-IU		4 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology, Efficient H.265+ compression technology, Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 66,890,000
DS-2CD2143G0-IS (Black)		4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB S: Audio/Alarm IO connectors	call
DS-2CD2143G0-IU		4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP66 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone	call
DS-2CD2145FWD-IS		4 MP Powered-by-DarkFighter Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -S: audio and alarm interface available	IRR 49,060,000
DS-2CD2146G2-I		4 MP AcuSense Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning	IRR 49,240,000
DS-2CD2147G2-LSU (2.8mm)		4 MP ColorVu Fixed Dome Network Camera, High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology 24/7 colorful imaging Focus on human and vehicle targets classification based on deep learning -SU: Built-in microphone for real-time audio security, audio and alarm interface available	IRR 85,000,000
DS-2CD2163G0-IS		6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	call
DS-2CD2163G0-IS (Black)		6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 43,680,000
DS-2CD2163G0-IU		6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 x 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Built-in microphone	IRR 44,600,000
DS-2CD2163G2-IU (2.8mm)		6 MP AcuSense Vandal Fixed Dome Network Camera High quality imaging with 6 MP resolution Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security	IRR 70,780,000
DS-2CD2183G0-IU		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP66, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone	call
DS-2CD2183G2-IU		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB - 1/2.8" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+ - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone, Up to 30 m IR range	IRR 74,280,000
DS-2CD2183G0-IS (Black)		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 x 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 47,840,000



















DS-2CD2185FWD-I		<p>4K Fixed Dome Network Camera</p> <p>High quality imaging with 8 MP resolution, Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p> <p>Water and dust resistant (IP67) and vandal proof (IK10)</p> <p>Robust structure design with full metal materials.</p>	IRR 108,460,000
DS-2CD2186G2-I (2.8mm)		<p>4K Acusense Fixed Dome Network Camera, High quality imaging with 8 MP resolution</p> <p>Excellent low-light performance via powered-by-DarkFighter technology</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p> <p>Focus on human and vehicle targets classification based on deep learning</p> <p>Built-in microphone for real-time audio security (-SU)</p> <p>Audio and alarm interface available(-SU)</p> <p>Water and dust resistant (IP67) and vandal resistant (IK10)</p>	IRR 65,930,000
<b>Bullet Series</b>			
DS-2CD2T43G2-2I (2.8mm)		<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+,Three streams,120dB WDR,Focus on human and vehicle targets classification based on deep learning,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 60m IR range</p>	IRR 66,970,000
DS-2CD2T43G2-2I (4mm)		<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+,Three streams,120dB WDR,Focus on human and vehicle targets classification based on deep learning,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 60m IR range</p>	IRR 66,970,000
DS-2CD2T43G2-4I (2.8mm)		<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,4mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+,Three streams,120dB WDR,Focus on human and vehicle targets classification based on deep learning,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 80m IR range</p>	IRR 72,380,000
DS-2CD2T43G0-I5		<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range</p>	IRR 76,140,000
DS-2CD2T43G0-I8		<p>1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range</p>	IRR 78,760,000
DS-2CD2T47G2-L		<p>4 MP ColorVu Fixed Bullet Network Camera</p> <p>High quality imaging with 4 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong backlight due to 130 dB WDR technology</p> <p>Focus on human and vehicle targets classification based on deep learning</p>	IRR 95,580,000
DS-2CD2T63G0-I8		<p>6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range</p>	IRR 52,700,000
DS-2CD2T63G2-4I		<p>High quality imaging with 6 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong backlight due to 120 dB WDR technology</p> <p>Focusing on human and vehicle classification based on deep learning</p> <p>Water and dust resistant (IP67)</p>	IRR 80,860,000
DS-2CD2T66G2-2I		<p>6 MP AcuSense Fixed Bullet Network Camera</p> <p>High quality imaging with 6 MP resolution</p> <p>Excellent low-light performance with powered-by-DarkFighter technology</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p>	call
DS-2CD2T66G2-4I		<p>6 MP AcuSense Fixed Bullet Network Camera</p> <p>High quality imaging with 6 MP resolution</p> <p>Excellent low-light performance with powered-by-DarkFighter technology</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology</p>	IRR 93,180,000
DS-2CD2T87G2-LK		<p>4 K ColorVu Fixed Bullet Network Camera</p> <ul style="list-style-type: none"> <li>High quality imaging with 8 MP resolution</li> <li>Efficient H.265+ compression technology</li> <li>Clear imaging against strong back light due to 130 dB WDR technology</li> <li>Focus on human and vehicle classification based on deep learning</li> </ul>	IRR 113,860,000
DS-2CD2T83G0-I5		<p>8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G</p>	call
DS-2CD2T85G1-I8		<p>8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range</p>	IRR 134,730,000
DS-2CD2683G2-I2S		<p>8 MP AcuSense Motorized Varifocal Bullet Network Camera</p> <p>High quality imaging with 8 MP resolution</p> <p>Motorized varifocal lens for easy installation and monitoring</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong backlight due to 120 dB true WDR technology</p> <p>Focus on human and vehicle targets classification based on deep learning</p> <p>Audio and alarm interface available</p> <p>Water and dust resistant (IP67) and vandal-resistant (IK10)</p>	IRR 139,300,000
DS-2CD2T83G2-4I		<p>High quality imaging with 8 MP resolution</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong backlight due to 120 dB WDR technology</p> <p>Focusing on human and vehicle classification based on deep learning</p> <p>Water and dust resistant (IP67)</p>	IRR 93,900,000
DS-2CD2T86G2-4I (2.8mm)		<p>4K AcuSense Fixed Bullet Network Camera</p> <p>High quality imaging with 8 MP resolution</p> <p>Excellent low-light performance with powered-by-DarkFighter technology</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light by 120 dB true WDR technology</p>	IRR 107,470,000
DS-2CD2T86G2-4I (4mm)		<p>4K AcuSense Fixed Bullet Network Camera</p> <p>High quality imaging with 8 MP resolution</p> <p>Excellent low-light performance with powered-by-DarkFighter technology</p> <p>Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light by 120 dB true WDR technology</p> <p>Focus on human and vehicle targets classification based on deep learning</p>	call
<b>Mini Dome Series</b>			
DS-2CD2523G0-IS		<p>1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO</p>	call
DS-2CD2525FWD-I		<p>2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera, High quality imaging with 2 MP resolution</p> <p>Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology</p> <p>Clear imaging against strong back light due to 120 dB true WDR technology, -W: Wi-Fi connection</p> <p>-S: built-in microphone, audio and alarm interface available</p> <p>Water and dust resistant (IP66) and vandal proof (IK08), Mini size suitable for limited space</p>	call
DS-2CD2542FWD-IS		<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), Hik-Connect cloud service-S: Built-in MIC, audio/alarm IO</p>	call



DS-2CD2543G0-IS		1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	call
DS-2CD2563G0-IS		1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	call
<b>Lite Bullet Vari-Facal Motorized Series</b>			
DS-2CD1623G0-I		2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	Call
DS-2CD1623G0-IZ		2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 x 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 95,560,000
DS-2CD1643G0-IZ		4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 x 1440@20fps, Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67 - H.265+, H.265, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	IRR 81,350,000
DS-2CD1653G0-I		1/3" progressive scan CMOS - BLC/3D DNR/ROI 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67 H.265+, H.265, H.264+, H.264 - 120 dB WDR Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	call
<b>Lite Dome Vari-Facal Series</b>			
DS-2CD1723G0-I		2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 x 1080@30fps - Up to 30 m IR range - 2.8 mm to 12 mm manual vari-focal lens - PoE (Power over Ethernet) - IP67, IK10 - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR	call
DS-2CD1743G0-I		4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps - Up to 30 m IR range, 2.8 mm to 12 mm manual vari-focal lens, PoE (Power over Ethernet) - IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB True WDR	call
DS-2CD1743G0-IZ		4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 x 1440@20fps - Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z:Motorized VF lens	IRR 91,340,000
DS-2CD1753G0-IZ		5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution, Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range	IRR 98,470,000
DS-2CD1753G0-I		5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution, Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range	call
<b>Bullet Vari-Facal Motorized Series</b>			
DS-2CD2625FWD-IZS		2MP Powered by DarkFighter Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP66) and vandal proof (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials.	IRR 110,210,000
DS-2CD2643G2-IZS		4 MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology, (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification based on deep learning	IRR 132,760,000
<b>Dome Vari-Facal Motorized Series</b>			
DS-2CD2783G2-IZS		8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x 2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 137,470,000
DS-2CD2785G1-IZS		4K AcuSense Varifocal Dome Network Camera, High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available, Water and dust resistant (IP66) and vandal proof (IK10)	IRR 150,320,000
<b>Fish Eye Series</b>			
DS-2CD2955FWD-I		5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range	IRR 126,380,000
DS-2CD2955FWD-IS		5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 102,960,000
DS-2CD6332FWD-IS		1/3" Progressive Scan CMOS Max. 2048 x 1536 @30fps Up to 15 live view display modes, 120dB WDR Up to 15m IR range, Built-in microphone and speaker 2 behavior analyses, 1 statistic	IRR 178,300,000
<b>people counting</b>			
iDS-2CD6412FWD/C		1.3MP, 2.1mm 115degree Fixed Lens 1/3" CMOS, 30 fps at 1280 x 960, People Counting, WDR 120dB, 3D DNR Electronic Day/Night, H.264, MJPEG, MPEG4, Alarm I/O ONVIF, PSIA, CGI, ISAPI, Support real-time people entering/exiting data. Support statistical traffic report based on configurable time interval (day/week/month/year). Support Smart Codec, high bandwidth efficiency, low time delay and optimized bit rate. Support on-board storage, Micro SD/SDHC/SDXC up to 128GB, card not included. Defog, Electronic Image Stabilization, various BLC modes. Support Smart Detection, including: Intrusion Detection, Audio Exception Detection, etc.	IRR 224,880,000
<b>Cube Smart Series</b>			
DS-2CD2420F-I(W)		Up to 2 megapixel (1920 x 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB - IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker - Support Wi-Fi, support WPS configuration with one touch - Support PIR (Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter	call

DS-2CD2421G0-IW		1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ DWDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	call
DS-2CD2423G0-IW		1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 61,130,000
DS-2CD2443G0-IW		1/3" Progressive Scan CMOS - 2688 x 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	call
<b>Pin Hole Series</b>			
DS-2CD2D14WD		1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	call
<b>2Q Smart Series</b>			
DS-2CD2Q10FD-IW		1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	IRR 31,300,000
<b>2U Smart Series</b>			
DS-2CV2U21FD-IW		2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 21,790,000
<b>IP PTZ Camera</b>			
DS-2DE4A225W-DE		4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by, DarkFighter technology, Clear imaging against strong back lighting due to 120 dB WDR technology, Pan and tilt ability enables camera to monitor zones of interest, 25x optical zoom allows for closer viewing of subjects in expansive areas, Up to 50m IR range ensures safety at night (IP66)	IRR 124,900,000
DS-2DE4A320W-DE		1/2.8" Progressive Scan CMOS - Up to 2048 x 1536 Resolution - 20x Optical Zoom, 16x Digital Zoom - WDR, 3D DNR, HLC, Smart IR - Basic Smart Suite Analytics - Up to 165 ft (50 m) IR Distance - H.265+ Video Compression Supported - IP66 Protection - 12 VDC and PoE+ (802.3at, class 4)	IRR 274,170,000
DS-2DE4220W-DE		2MP 20x Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W: 0.02lux/F1.5, Optical Zoom: 20x, Focus: 4.7-94.0mm, Digital Zoom: 16X, Pan range: 360° endless; Tilt range: -15°-90° (Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	call
DS-2DE4225W-DE-S6		4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome 1/2.8" progressive scan CMOS, High quality imaging with 2 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 25x optical zoom and 16x digital zoom provide close up views over expansive areas WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus Expansive night view with up to 100 m IR distance	IRR 222,510,000
DS-2DE4225W-DE-T5		2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS Up to 1920 x 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 214,590,000
DS-2DE4425W-DE-T5		4MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS Up to 2560 x 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 252,150,000
DS-2DF823615W-AELW		Optical Defog 2MP (1920*1080) Full HD 36X Optical Zoom Ultra-low illumination, 120db True WDR Smart Tracking, Smart Detection EIS (Electronic Image Stabilization) 500m IR distance Optional wiper(-W)	IRR 1,143,020,000
DS-2DE5220W-AE		2.54cm(1/2.8") Progressive Scan CMOS Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, Digital WDR 3D intelligent positioning function, Up to 150 m IR distance Hi-PoE/24 VAC power supply, Support H.265 video compression	IRR 338,660,000
DS-2DE5432W-AE-S5		1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus Up to 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm. Face capture: Up to 5	IRR 229,040,000
DS-2DE5230W-AE		2MP 30x Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W: 0.01lux/F1.6, Optical Zoom 30x, Focus: 4.3-129.0mm, Digital Zoom: 16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	call
DS-2DF5276-AEL		1/3" progressive Scan cmos 30x / 20x optical Zoom, 16x digital Zoom Smart tracking, eis, defog True day/Night, D wdr, 3D DNR 3D Intelligent positioning, Connectivity Technology: Wireless	IRR 447,450,000
DS-2DF5276-AE3		1/3" Progressive Scan CMOS 30X optical zoom, 16x digital zoom, ONVIF Smart Tracking, EIS, Defog, True Day/Night, D WDR, 3D DNR 3D intelligent positioning, Triple stream 24VAC / High-PoE power supply, Outdoor / Indoor	IRR 562,530,000
DS-2DF6A236X-AEL		6-inch 2 MP 36X DarkFighter Network Speed Dome High quality imaging with 2 MP resolution Excellent low-light performance via DarkFighter technology 36x optical zoom provides close up views over expansive areas Intelligent functions based on deep learning Water and dust resistant (IP67) and vandal proof (IK10).	IRR 520,800,000
DS-2CDE5432W-AE		4-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus	IRR 229,050,000

DS-2CD5220W-AE		2MP 20X Network IR PTZ Dome Camera <ul style="list-style-type: none"> <li>▣ 1920 x 1080, 1/2.8" Progressive Scan CMOS</li> <li>▣ 20X Optical Zoom</li> <li>▣ DWDR, ▣ 3D intelligent positioning function</li> <li>▣ Support cloud P2P</li> <li>▣ Up to 150m IR distance</li> </ul>	IRR 231,170,000
DS-2DE7232W-AE		2MP 32x Network IR Speed Dome, Up to 1920 x 1080@60fps resolution, Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR, 32x optical zoom, 16x digital zoom, WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus, Up to 150 m IR distance, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression	call
<b>NVR-Monitor</b>			
DS-7600NI-E1/A		Advertising files import and preview, The output resolution of LCD is up to 1080P. Third party network cameras supported, Up to 8-ch synchronous playback at 720P resolution, Up to 8 network cameras can be connected, Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 164,300,000
<b>NVR 4 Channel</b>			
DS-7104NI-Q1/M		IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call
DS-7104NI-Q1		4-ch Mini 1U NVR H.265+/H.265/H.264+/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs Up to 4-ch 1080n decoding capability	call
DS-7104NI-Q1/4P/M		IP video input : 4-ch / 4-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call
DS-7604NI-Q1		IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call
DS-7604NI-Q1/4P		IP video input : 4-ch / 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call
DS-7604NI-K1		IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 61,560,000
DS-7604NI-K1/4P		IP video input : 4-ch - 4-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 82,740,000
<b>NVR 8 Channel</b>			
DS-7108NI-Q1/M		IP video input : 8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 49,380,000
DS-7108NI-Q1/8P/M		IP video input : 8-ch / 8-ch POE Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 x 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call
DS-7608NI-Q2/8P		IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	call
DS-7608NI-Q1		Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	call
DS-7608NI-Q2		Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	call
DS-7608NI-K1		IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 68,340,000
DS-7608NI-K1/8P		8-ch 1U 8 PoE 4K NVR Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 126,190,000
DS-7608NI-K2		Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity 1 HDMI and 1 VGA interfaces, both interfaces support independent video output 2 SATA interfaces for HDD connection (up to 10 TB capacity per HDD)	IRR 71,200,000
DS-7608NI-K2/8P		IP video input : 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	call
<b>NVR 16 Channel</b>			
DS-7616NI-Q1		IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call
DS-7616NI-Q2		IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 89,810,000
DS-7616NI-Q2/16P		IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 107,470,000
DS-7616NI-K1		Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity Up to 160 Mbps incoming bandwidth	IRR 74,000,000

DS-7616NI-K2		IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 82,970,000
DS-7616NI-K2/16P		IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 162,340,000
DS-7716NI-Q4		IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	call
DS-7716NI-Q4/16P		IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 255,140,000
DS-7716NI-K4		IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 211,190,000
DS-7716NI-K4/16P		IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	call
<b>Network Video Recorders- Ultra Series</b>			
DS-8616NI-K8		16-ch 2U 4K NVR, Up to 16 channel IP cameras can be connected, Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces, 8 HDD can be used for continuous video recording, Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	IRR 147,000,000
<b>NVR 32 Channel</b>			
DS-7732NI-Q4		IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	call
IDS-7732NXI-I4/8S		32-ch 1.5U 4K DeepinMind NVR, H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on deep learning algorithm Up to 16-ch perimeter protection Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture Up to 8-ch video structuralization, Up to 32-ch IP cameras can be connected Up to 16-ch 1080p decoding capability	IRR 719,160,000
DS-7732NI-Q4/16P		IP video input : 32-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 170,000,000
DS-7732NI-K4		IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 210,450,000
DS-7732NI-K4/16P		IP video input : 32-ch - 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 334,310,000
DS-8632NI-K8		Up to 32 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264/MPEG4 video formats Up to 4K high-definition live view, storage and playback Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	call
DS-9632NXI-I8/S		32-ch 2U 4K NVR, Up to 32 channel IP cameras can be connected, Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 739,020,000
DS-9632NI-I16		32-ch 3U 4K NVR Up to 32 channel IP cameras can be connected Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	call
IDS-9632NXI-I8/4F		• Facial Recognition and Comparison, • Face Picture Library: 16 Libraries, 100,000 Pictures • Face Capture Analysis, Classification and Comparison and Alarm, • 4-ch Face Pictures Comparison Alarm, Alarm Linkage Actions: Recording, Audio Warning, Notify Surveillance Center, Send E-mail, • Face Picture Search, False Alarm Filtering • Up to 32 Channel IP Video Input • Incoming Bandwidth 256 Mbps, Outgoing Bandwidth 200 Mbps • Recording Resolution up to 12 MP, • Synchronous 2-ch HDMI, 2-ch VGA and HDMI1 4 K (3840 × 2160) Resolution • H.265+/H.265/H.264+/H.264/MPEG4, Self-Adaptive Video Formatting	IRR 3,213,890,000
DS-9664NXI-I8/S		64-ch 2U 4K NVR Up to 64 channel IP cameras can be connected Up to 12 MP high-definition live view, storage and playback Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 968,630,000
DS-9664NI-I16		64-ch 3U 4K NVR Up to 64 channel IP cameras can be connected Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in poor network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	call