PRICE LIST

HIKVISION

فرومگاه سلیمانی

Turbo HD Camera - DVR

Items		Description Turbo HD - 2MP	User Price
DS-2CE16D0T-EXIF		2 MP Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 x 1080 resolution 2.8 mm, 3.6 mm fixed lens, DWDR, ZDDNR Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (T966)	IRR 12,980,000
DS-2CE16D0T-ITFS		2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable, EXIT 22: a dvanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 17,620,000
DS-2CE10DFT-F ColorVu		2 MP ColorVu Fixed Mini Bullet Camera 2 MP full time color bullet camera, 24/7 full color imaging, Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images, Water and dust resistant (IP67) 4 in 14 d signals switchalle TUXHADCVICVEDS)	IRR 24,220,000
DS-2CE10DF3T-FS		2 MP ColorVU Audio Fixed Mini Bullet Camera High quality imaging with 2 MP, 1520, v180 resolution 247 doing with 2 MP, 1520, v180 resolution Clear imaging against strong back (gift dui to 1 30 doi 80 true WDR technology 3D DNR technology delivers clean and sharp images, 2.8 mm, 3.6 mm fixed focal lens Up to 20 m while light duitainse for bright innight imaging High quality audio with audio over coasial cable, bull-in mic One port for four switchable signals (TVLMD/DVLV/UVSIS) Water and dust resistant (IP67)	IRR 34,070,000
DS-2CE10DF3T-F		DS-2CE10DF3T-F Turbo HD Products Turbo HD Cameras Turbo HD Cameras with ColorVu 2 MP ColorVu Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images	IRR 21,020,000
DS-2CE12DF3T-F ColorVu		2 MP Color/tu Fixed Bullet Camera 24/7 full color imaging, Warm supplemental light with 40 m range 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images. Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 29,610,000
DS-2CE12DF3T-FS 2.8MM		High quarky many wint 2 MP, 1920 X 1030 resolution	IRR 38,330,000
DS-2CE16D0T-EXIP		2MP Outdoor EXIR Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 x 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging, DWDR,2DDNR Water and dust resistant (1966),	call
DS-2CE16D0T-EXIPF 2.8mm		2 MP Fixed Mini Bullet Camera,High quality imaging with 2 MP, 1920 x 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright ningsing One port for four switchable signals (TVIXHD/CVI/CVBS) Water and dust resistant (IP66)	IRR 13,390,000
DS-2CE16D0T-ITF		2 MP Fixed Mini Bullet Camera 2 MP bullet Camera Smart IR: up to 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVUCVBS)	call
DS-2CE16D0T-ITPF		2 MP Fixed Mini Bullet Camera 2 MP, 1920 × 1080 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens 4 in 1 video output (withhabe TV/LHO/CV/CVBS) Smart IR, up to 25 m IR distance, DWDR,HLC,BLC IP67	IRR 10,430,000
DS-2CE16D0T-ITPFS		2 MP Audo Fixed Mini Bullet Camera 2 MP coasilia audio camera Enhancing safety with discreet and economical bulli-in microphone Transmits audio over the coasia cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and dust resistant (P67)	IRR 16,390,000
DS-2CE16D0T-VFIR3F		2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 28,780,000
DS-2CE76D0T-ITPF		2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 11,250,000
DS-2CE76D0T-ITPFS		2 MP Audio Fixed Turret Camera 2 MP coaxial audio camera, Enhancing safety with discreet and economical built-in microphone, Transmits audio over the coaxial cable. EXIR 2.0: advanced infrared technology with 30 m R distance, Vader and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 14,840,000
DS-2CE76D0T-ITMF		2 MP Fixed Turret Camera 2 MP hurret camera EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TV/UHD/CVUCVBS).	IRR 16,440,000
DS-2CE76D0T-ITMFS		2 MP coaxial audio camera Enhancing sately with discrete and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrance technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 18,810,000
DS-2CE76D0T-EXIPF		 ☐ High quality imaging with 2 MP, 1920 x 1080 resolution ☐ 2.8 mm, 3.6 mm fixed lens ☐ Up to 20 m IR distance for bright night imaging ☐ One port for four switchable signals (TVI/AHD/CVI/CVBS) 	IRR 13,390,000

DS-2CE70DF0T-PF ColorVu	and the second s	2 MP ColorVu Indoor Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution, 24/7 color imaging with F1.0 aperture 3D DNR technology delivers clean and sharp images.2 & mm, 36 mm, 6 mm/fixed focal lens Up to 20 m while light distance for bright night imaging One port for four switchable signals (TVI4MHD/CVI4/CVBS)	IRR 20,730,000
DS-2CE70DF3T-PF	and the second sec	One port for four switchades signals (1VIAHD/CVI/CVIS) 2 MP ColorVI Fixed Turret Comera High quality imaging with 2 MP, 1920 × 1080 resolution, 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 190 dB true WDR technology 30 DNR technology delivers clean and sharp images, 28 mm, 36 mm, 5 mm fixed rocal lens Up to 20 m while light distance for bright might imaging One port for urs witchades signals (TVIAHD/CVI/CVIS)	IRR 26,980,000
DS-2CE72DF3T-F		2 MP Color/V Fixed Turret Camera, High quality imaging with 2 MP, 1920 x 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back tight due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Up to 40 m while leight distance for bright night imaging One port for four switchable signals (TVIAHDC/VICVBS) Water and dust resistant (IP67)	IRR 25,410,000
DS-2CE72KF0T-FS		High quality imaging with 3K, 2960 × 1665 resolution 24/7 colour imaging with F1.0 aperture 2.8 mm, 36 mm fxed focal fine fine financing Up to 40 m white light distance for bright night imaging High quality audio with audio over coaxia cable, built-in mic One port for four switchable signals (TVIAHDC/VICVBS) Water and dust resistant (TP67)	IRR 37,400,000
DS-2CE72DFT-F		2 MP Color VI Fixed Turrer Camina 2 MP full imp color turrer camera 24/7 full color imaging Warm supplemental light with 20 m range Clear imaging even a gainst strong back (ghining due to 130 dB true WDR technology 3D DIR technology delivers clean and sharp images Water and dust resistant (P67)	IRR 17,290,000
DS-2CE72DFT-FC			IRR 10,520,000
DS-2CE10KF0T-FS		1934 Cold'or Judio Fixed Mini Builet Camera High quality imaging with 3X, 2960 × 1656 resolution 2447 color imaging with F10 aperture 2.8 mm, 3.6 mm Rixed focal lens Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVIAHDCVICVES) Water and dust resistant (IP67)	IRR 38,370,000
DS-2CE12KF0T-FS		Mich audie, au	IRR 40,260,000
DS-2CE56D0T-VFIR3F		2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 32,240,000
DS-2CE76D3T-ITPF (NEW)		Turbo HD - 2MP - Ultra Low Light Series 2 MP Ultra Low Light Indoor Fixed Turet Camera, 2 MP turet camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB ture VDR technology 20 delivers clean and sharp images, EXIR 2.0: advanced infrared technology with 30 m IR distance, 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 17,420,000
DS-2CE16D3T-ITF		2 MP Ultra Low Light Fixed Mini Bullet Camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67). 4 H (4 signals switchable TVI/AHD/CV/UCVBS).	IRR 21,660,000
DS-2CE16D3T-IT3F	ana -	2 MP bullet camera 2 MP bullet camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 50 mI R distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TV/MIADICVI/CVI/S)	IRR 19,670,000
DS-2CE16D8T-IT3E	0 Max	2 MP Utra Low Light PoC Fixed Builter Camera 2 MP high performance builter camera Strong night performance, capturing images in uttra-low light down to 0.003 lux Clear imaging even against strong back lighting due to 150 dB true VMDR technology 30 DINR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 60 m IR distance Water and dust resistant (PFo7)	IRR 21,600,000
DS-2CE16D3T-I3F		Transmits both HD video and power over the same coaxial cable 2 MP high-performance CMOS. Ultra low light. 1920 x 1080 resolution . 2.8 mm, 3.6 mm, 6 mm fixed lens. Smart IR, up to 30 m IR distance . OSD menu, 3D DNR, 120 dB true WDR, day/night switch. 4 in 1 video output (switchable TVI/AHD/CVI/CVBS).IP67.Up the coax (HIKVISION-C)	IRR 12,400,000
		Turbo HD - 5MP	
DS-2CE16H0T-ITF		5 MP Fixed Mini Bullet Camera, 5 MP bullet camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TV/AHD/CVI/CVIS)	IRR 19,470,000
DS-2CE16H0T-ITFS		5 MP Audio Fixed Mini Bullet Camera, 5 MP coaxial audio camera Enhanced safety with discreet and economical built-m microphone, Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m R distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVIS)	IRR 23,050,000
DS-2CE16H0T-ITPFS		5 MP Audio Fixed Mini Bullet Camera 5 MP Coasilia audio camera Enhanced saflety with discrete and economical bull-in microphone Transmit audio over coaxia cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and t-usi resistant (P67)	IRR 20,770,000
DS-2CE16H0T-ITPF		6 MP Fixed Mini Bulke Camera 6 MP bulke camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TV/IAHD/CV/ICVBS)	call
DS-2CE16H0T-IT1F		5 MP high performance COMS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	call
DS-2CE17H0T-IT1F	() ()	5 MP Fixed Bullet Camera High quainging with 5 MP, 2560 x 1944 resolution 2,4 mm, 2,8 mm, 3 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVL4HDCVI/CVBS) Water and dust resistant (IP67)	IRR 23,230,000
DS-2CE17H0T-IT3F	() ())	5 MP Fixed Builter Camera High quality imaging with 5 MP, 2560 x 1944 resolution 2.8 mm, 3.6 mm, 6 mm, 8mm, 12mm fixed local lens Up to 40 m IR distance for bright night imaging One port frour switchable signals (TVLAHDCVI/VBS) Water and dust resistant (IP67	IRR 23,300,000

		High quality imaging with 5 MP, 2560 \times 1944 resolution	
DS-2CE17H0T-IT3FS		2.8 mm, 3.6 mm, fear fixed focal lens Up to 40 m Ri distance for bight night imaging One port for four switchable signals (TVIAHDC/VICVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic	IRR 29,790,000
DS-2CE17H0T-IT5F	and the	5 MP Fixed Builter Camera High quality imaging with 5 MP, 2560 x 1944 resolution 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Up to 80 m IR distance for bright night imaging One port for fours witchable signals (TVIAHDCVILVBS) Water and dust resistant (IP67)	call
DS-2CE16H0T-IT3F	ar (5 MP high performance COMS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	call
DS-2CE16H0T-IT5F	()	5 MP high performance COMS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVIC/VBS) - IP67	call
DS-2CE16H0T-IT3ZF		5 MP high performance COMS - 2560 x 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	call
DS-2CE17D0T-IT1F	0 2× 7	2 MP Fixed Bullet Camera High quality imaging with 2 MP, 1920 x 1080 resolution 2,8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for low switchable signals (TVLAHDDCVIVCVBS) Water and dust resistant (IP67)	IRR 18,050,000
DS-2CE17D0T-IT3F	0 - 7	2 MP Fixed Bullet Camera High quality imaging with 2 MP; 1920 x 1080 resolution 2.8 mm, 5.0 mm, 6 mm, 12 mm fixed local lens Up to 40 m IR distance for bright night imaging One port for low switchable signals (TVLHADDCVIVCVBS) Water and dust resistant (IP67)	IRR 23,160,000
DS-2CE10HFT-F28	() nine (5 MP Color/v Erixed Mini Bullet Camera, 5 MP full time color bullet camera 2477 full color imaging, 24 mm tixed incola lens Warm supplemental light with 20 m range Clear imaging even against strop back tighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dus tresistant (PF67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 34,810,000
DS-2CE10DF0T-F	Nora	2 MP ColorVu Fixed Mini Bullet Camera. High quality imaging with 2 MP, 1920 x 1080 resolution. 2477 color imaging with F1.0 aperture. 3D DNR technology delivers clean and sharp images. 2.8 mm, 3.6 mm, 6 mmfixed focal lens. Up to 20 m white light distance for bright night imaging.	IRR 28,420,000
DS-2CE12HFT-F28 2.8mm		5 MP Color/U Fixed Bullet Camera, 5 MP full time color bullet camera 24/7 full color imaging, 2.8 mm fixed focal lens Warm supplemental light with 40 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dus tresistant (P67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 40,160,000
DS-2CE72HFT-F28		5 MP Color/Vu Fixed Turret Camera, 5 MP full time color turret camera 24/7 full color imaging, 2.6 mm fixed focal lens Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67), 4 h 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 38,370,000
DS-2CE76H0T-ITMF		5 MP coaxial - Enhanced safety with discreet and economical Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67),4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 21,440,000
DS-2CE76H0T-ITMFS		5 MP coaxial audio camera. Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67),4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 24,290,000
DS-2CE76H0T-ITPF		5 MP Indoor Fixed Turret Camera 5 MP Jurret camera EXIR 2.0: advanced infraret technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 16,300,000
DS-2CE78D0T-IT3FS	6	2 MP Audio Fixed Turret Camera, 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 40 m IR distance Water and Aust resistant (P67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	call
DS-2CE76D3T-ITMF	and the second s	2 MP Ultra Low Light Fixed Turret Camera, 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR.2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 23,840,000
DS-2CE78D0T-ITFS	and the second s		call
DS-2CE76H0T-ITPFS		5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AID/CVI/VDS5)	IRR 20,280,000
DS-2CE78H0T-IT1F 2.4mm		5 MP Camera 5 MP 2560 x 1944 resolution 2.4 mm, 2.8 mm, 35 mm, 6 mm fixed focal lens Smart IR, up to 30 m IR distance 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67	IRR 23,860,000
DS-72HFT-F28		5 MP Color/Vu Fixed Turret Camera, 5 MP full time color turret camera 24/7 full color imaging, 2.8 mm fixed focal lens Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3B DIN technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchabe TVI/AHD/CVUCVBS).	IRR 28,920,000
DS-2CE78H0T-IT3F©		5 MP turret camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and Aust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 25,790,000
DS-2CE56H0T-ITMF	6	5 MP high performance COMS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 5.6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVICVBS) - IP67	call

DS-2CE56H0T-IT1F	0	5 MP high performance COMS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	call
DS-2CE56H0T-IT3F	6	5 MP high performance COMS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	call
DS-2CE56H0T-IT3ZF		5 MP high performance COMS - 2560 x 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVVAHD/CVICVBS) - IP67	call
		TURBO HD 5MP (TURBO HD 5.0) PIR Series	
DS-2CE71H0T-PIRL		5 MP high performance CMOS - 2560 x 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	call
		Turbo HD - 8MP	
DS-2CE78U8T-IT3		4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 x 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 63,870,000
DS-2CE18U8T-IT3		4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 x 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	call
		Turbo HD PTZ Camera	
DS-2AE4225TI-D	6	High quality imaging with 2 MP resolution - Excellent low-light performance via powered-by-DarkFighter technology -Clear imaging against strong back lighting due to 120 dB WDR technology - Pan and tilt ability enables camera to monitor zones of interest - 25 x optical zoom allows for closer viewing of subjects in expansive areas - Up to 100 m IR range ensures safety at night - Water and dust resistant (IP66)	call
DS-2AE5223TI-A (24VAC)	e	1/3° CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05/ux/F1.4, B/W:0.005/ux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15 90° (Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	call
DS-2AE7230TI-A (24VAC)	5.	High performance 1/3° CMOS - Max. image resolution: 1920 x 1080 - Min. illumination: Color: 0.05Lux @ (F1.6, AGC ON); BW: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30x optical zoom, focal length 4-120mm - 16x digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	call
		Turbo HD DVR 1080p / 3MP / 4MP lite	
DS-7204HQHI-K1	- Imi	Analog video input 4-ch - Encoding resolution 4 MP like/3 MP/1080p/720p/VGAWD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP like resolution - <u>Frame rate</u> 4 MP like/3 MP/1080p/180720p/WD1/4CIF/VGA/CIF@25/ps (P)/30/ps (N) - <u>IP video input</u> : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265/H.265/H.264+/H.264 IP cameras - <u>HDM output</u> 1-ch, 1202 x 1080/06/Hz, - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity 4-ch 1080p 1U H.265 AcuSense DVR	call
IDS-7204HQHI-M1/S	74	4 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target dessification based on deep learning Efficient II-265 pro+ compression technology Encoding ability up to 1080p ⊜ 15 (ps.5 signals in guid adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 6 network cameras can be connected.	IRR 46,520,000
iDS-7204HUHI-M1		4-ch 5 MP 1U H.265 AcuSense DVR 4 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro- compression technology Encoding abily up to 8 MP (iii @ 15 fips, 5 MP @ 12 (ps 5 signals input adaptively (HDTVIA/HD/CVI/CVB2/P) Up to 8 network cameras can be comnected.	call
DS-7208HQHI-K1	and the second s	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGAWD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15(ps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25(ps (P)/30(ps (N) - I <u>P video input</u>) - 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265+/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 x 1080/60Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	call
IDS-7208HQHI-M1/S	744	8-ch 1080p 1U H.265 AcuSense DVR 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro- compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/P) Up to 12 network cameras can be connected.	IRR 71,290,000
DS-7208HUHI-M1/S	- Jon J	8-ch 5 MP 1U H.265 AcuSense DVR 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro- compression technology Encoding ability up b 8 MP @ 15 pt SMP @ 12 pts 5 signals input adaptively (HDTVIAHD/CVI/CVBS/P) Up to 16 network cameras can be connected.	IRR 120,610,000
DS-7116HQHI-K1	-	Anida video input 16-6n - Encoding resolution - 4 MP 1863 MP/1080/720p/VGAWD14/GIF/CIF - <u>Video compression</u> 1.465 Pro+H.265 Pro+H.265H.244+H.264 - Full channel recording at up to 4 MP liter 3 MP/1080/720p/VGAWD14/GIF/CIF - <u>Video compression</u> 1.465 Pro+H.265H.264+H.264 - Full channel recording at up to 1 MP liter 3 MP/1081/Filer; 140P liter 370/WD114/GIF/CIF - <u>Video compression</u> (N) - Privideo input : 8ch up to 24-ch Up to 6 MP resolution - <u>Encording at up to 1 MP liter</u> 3 MP/1081/Filer; 140P liter 370/WD114/GIF/CIF/ACIF@251ps (P)30/PG (N) - Privideo input : 8ch up to 24-ch Up to 6 MP resolution - Support H.265+H.264+H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (344 v 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 6 TB capacity	call
IDS-7216HUHI-M2/S	- Bart	16-ch 5 MP UI A265 AcuSense DVR Deep learning-based motion detection 2.0 for all analog channels Deep learning-based perimeter protection Efficient H.265 pro- compression technology Encoding ability up to 8 MP @ 15, 5 MP @ 12 (ps 5 signals input adaptivek) (HDTVIAHD/CVI/CVBS/IP) Up to 32 network cameras can be connected	IRR 224,090,000
ids-7216HQHI-M1/S	- I'm'	16-ch 1080p 1U H.265 AcuSense DVR 16 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro- compression technology Encoding ability up to 1080p (9 15 fps Encoding ability up to 1080p (9 15 fps 5 signals input adaptively (HDTVL/AHD/CV/UCVBS/P) Up to 24 network.cameras can be connected.	IRR 109,770,000
IDS-7216HQHI-M2/S	and a second	Record from and Manage up to 16 Cameras Supports up to 8 JP Channels Up to 2MP Recording Resolution 20TB HDD Capacity (Available Separately) H.265+H264+H.265H.240 Video Codecs Two-Way Audio HDMI & Vicko Video Cutputs	IRR 151,150,000
7216HQHI-K1-Eco		Analog video input 16-ch - Encoding resolution 4 MP liter3 MP/1080/pr/20p/VGAWD14/GIFC/E - Video compression H.265 Pro+H.265 ProH.265/H.264-H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD14/CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265/H.265/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - <u>ECC CASE</u>	call
DS-7216HQHI-K1		Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGAWD1/4ClF/ClF - Video contretession H.265 Pro+/H.265 Pro+/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> 4 MP lite@15fps; 1080p lite/720p/WD1/4ClF/VGA/ClF@25fps (P):30fps (N) - <u>IP video input</u> 3 ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.265+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 121,800,000
DS-7208HGHI-F1	Contraction of the local division of the loc	8-ch 1080p Lite 1U H 254 DVR 8 channels and 1 HDD 1U DVR H 2644 / H 264 video compression Encoding ability up to 1080p lite (@ 25/30 fps 5 signals input adaptively (HDTV/HADC/VCVBS/IP) Up to 10 network cameras can be connected	call

DS-7208HGHI-F2		8-ch 1080p Lite 1U H.264 DVR 8 channels and 2 HDDs 1U DVR H.2644 / H.264 video compression Encoding ability up to 1080p lite (@ 25/30 fps 5 signals input adaptive(HDTV/HAD/VICVRS/IP) Up to 10 network cameras can be connected	call
DS-7216HGHI-K1	- Jail	16-ch 1080p Lite 1U H.265 DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0H.265 ProvH.265 ProvH.265 Video compressionHDTVI/AHD/CVI/CVBS/IP video inputAudio vigo cavaila clable Up to 18-ch IP camera inputs (up to 5 MP/Up to 1080p, Lite @15 fps encoding capability Max. 1200 mfor 720p HDTVI signal	call
DS-7216HQHI-K2	and a second sec	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGAWD 1/4CIF/CIF - Video compression H.265 Pro+H.265 ProH.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Erame rate</u> : 4 MP lite/9 15(ps: 1090p) lite/720p/WD1/4CIF/VGA/CIF @25(ps: (P)/30(ps: (N) - <u>IP video input</u> : ech (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265+/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	call
iDS-7232HQHI-M2/S	A ME A	32-ch 1080p TU H 265 AcuSense DVR Deep learning-based motion detection 2.0 for all analog channels Deep learning-based perimeter protection Efficient H.265 prot-compression technology Encoding ability up to 1080p @i 51 fps 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP) Up to 40 network cameras can be connoted	call
DS-7232HQHI-K2		Analog video input 32-ch - Encoding resolution 4 MP lite(3 MP/1080p720pV/GAWD1/4CIF/CIF - <u>Video compression</u> H 265 Pro+H-265 ProH-265/H-264+H-264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite (8 15/ps; 1080p lite/20pWD1/4CIF/VGA/CIF @25(ps; (P)/301ps; (N) - <u>IP video input</u>): 8ch (up to 40-ch) Up to 6 MP resolution - Support H 265+H-265+H-264+H-264 IP cameras - <u>HDMI output</u> 1-ch, K(3440 x 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 267,320,000
		Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite	
DS-7204HUHI-K1	- I and	Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H 265 Pro+H 265 H 265/H 264+H 264 - 8 MP @ 8 fps is only available for channel 1 of D5-7204HUH+K1 - <u>Frame rate</u> : 8 MP @ 8 fps/SMP @ 12 fps/3 MP @ 13 fps/3 MP @ 18 fps 1080p/720p/WD1/4CIF/VGA/CIF @ 25 fps (P)/30 fps (N) - I <u>P video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H 265/H 265/H 265/H 265/H 264 /H 264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 4- ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 67,720,000
DS-7208HUHI-K1	Come I	Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H:265 Pro+M:265 Pro+M:265 Pro+M:265 H:264+H:264 - <u>Frame</u> rate: 8 MP @8 fps/5MP @ 12 fps/4 MP @ 15 fps/3 MP @ 16 fps 1080p/720p/WD1/4CIF/VGA/CIF @ 25 fps (P)/30 fps (N) - <u>P video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H:265+H:265H:264+H:264 + D cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	call
iDS-7204HUHI-M1/S		4-ch 5 MP 1U H 265 AcuSense DVR, 4 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H 265 pro+ compression technology Encoding ability up to 8 MP lite @ 15 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHDCVICVBS/IP) Up to 8 network cameras can be connected.	IRR 74,720,000
IDS-7208HUHI-M1/S		8-ch 5 MP 1U H.265 AcuSense DVR, 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.255 pro-compression technology Encoding aduly up to 4 MP @ 8 1ps, 5 MP @ 12 (ps) 5 signals input adaptively (HDTV/AHD/CVCVCS8/IP). Up to 16 network cameras can be connected.	IRR 120,610,000
DS-7316HUHI-F4/N		Support HD-TVI, AHD and analog cameras with adaptive access 16 Composite Video Inputs, 1 Composite Video Output, 1 VGA Oupt AD Dual HOM Output TVT 2020 / 1600P, AHD 2020, IP Video Input: 2Ch up to 8MP Support 4 Units Sata Harddisk (Max 6TB per unit) Support USB Flash Drive Backup, Network Remote Recording & Back-up Remote Surveillance with IE Broswer & Moleile Phone Apps Support TCP/IP, PPPoE, DHCP, DDNS, UPnP, HTTPS & Hik Cloud P2P	call
DS-7216HUHI-K2	and the second s	Analog video input 16-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGACIF - <u>Video compression</u> H.265 Pro+H.265 Pro+H.265 H.264+/H.264 - Ename rate : 8 MP@8 tps/SMP@12 tps/4 MP@15 tps/3 MP@18 tps 1080p/720p/WD1/4CIF/VGACIF@25 tps (P)30 tps (N) - <u>P_video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265H.264+/H.264 P cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)30Hz - <u>Audio input</u> 4-ch, RCA - <u>Casacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 218,730,000
		Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)	
DS-7204HUHI-K1/P	and a second sec	Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGACIF - Video compression H-265 Pro+H-265 ProH-265H-264+H 264 - 8 MP@8 tps is only available for channel 1 of D5-720H/UH/K1 - Erame rate: 8 MP@8 tps5MP@12 fps4/ MP@13 fps1 Stp3 MP@13 tps1 Bps3 MP&13	IRR 67,470,000
DS-7208HUHI-K2/P	and the second s	Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+H.265 ProH.265/H.264+H.264 - Frame rate: 8 MP @8 tps/5MP@t 2 tps/4 MP@t5 tps/3 MP@t8 tps 1080p/720p/WD1/4CIF/VGA/CIF @25 tps (P)/01 0 tps/01. P video input : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265/H.264+H.264 IP cameras - <u>HDMI output 1-ch</u> . 4K (3404 v 2160)304E - <u>Audio input 4-ch</u> . RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable	IRR 115,230,000
		Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP	
DS-7204HTHI-K1		Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+H.265 Pro+H.265/H.264+H.264 - Full channel recording at up to 8 MP resolution - <u>Frame rate</u> : 8 MP@15 (ps, 5 MP@20 (ps, 3 MP@18 (ps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 (ps (P)/30 (ps (N) - <u>IP video</u> input: 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265/H.265/H.264/H.264 /P cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	call
DS-7208HTHI-K2		Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H-265 Pro+/H-265 ProH-265/H-264+/H-264 - <u>Frame</u> rate: 8 MP @ 15 fps, 5 MP @ 20 fps, 3 MP@ 18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF @ 25 fps (P)/30 fps (N) - <u>IP video nput</u> 8-ch (up to 16-ch) Up to 8 MP resolution - Support H-265/H-264+/H-264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160/30H - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	call